

Cod. 08412342

VRLA BATTERY AGM TECHNOLOGY

Revision 4.0

Specifications

Nominal Voltage (V) 12V

Nominal Capacity

20 hour rate	(1.9A to 10.50V)	38.0Ah
10 hour rate	(3.48A to 10.50V)	34.8Ah
5 hour rate	(6.55A to 10.20V)	32.75Ah
1 C	(23.3A to 9.60V)	25.3Ah

Weight Approx. 10.7kg (23.6 Lbs.)

Maximum Discharge Current for

5 seconds: 320A

Charging Methods at 25°C (77°F)

Cycle use:

Charging Voltage 14.4 to 15.0V

Coefficient -5.0mv/°C/cell

Maximum Charging Current: 8A

Standby use:

Float Charging Voltage 13.50 to 13.80V

Coefficient -3.0mv/°C/cell

Operating Temperature Range

Charge -15°C (5°F) to 40 °C (104°F)

Discharge -15°C (5°F) to 50 °C (122°F)

Storage -15°C (5°F) to 40 °C (104°F)

Charge Retention (shelf life) at 20°C (68°F)

1 month 92%

3 month 90%

6 month 80%

Case Material ABS UL94HB

(Option: ABS UL94 V-0 flame retardant)

Terminal FM6


Description of torque value of hard ware for the terminals:

Reccomended torque value M5: 2.94 N-m (30kg-cm)

Maximum allowable torque value M5: 4.90 N-m (50kg-cm)

ENERGY *Cyclic*
SAFE

Dimensions mm (inch)



Dimensions: mm. 195 x 130 x 160 H

